


SQLITE - LIKE CLAUSE

http://www.tutorialspoint.com/sqlite/sqlite_like_clause.htm

Copyright © tutorialspoint.com

The SQLite **LIKE** operator is used to match text values against a pattern using wildcards. If the search expression can be matched to the pattern expression, the LIKE operator will return true, which is 1. There are two wildcards used in conjunction with the LIKE operator:

- The percent sign
- The underscore 

The percent sign represents zero, one, or multiple numbers or characters. The underscore represents a single number or character. These symbols can be used in combinations.

Syntax:

The basic syntax of % and _ is as follows:

```
SELECT FROM table_name  
WHERE column LIKE 'XXXX%'
```

or

```
SELECT FROM table_name  
WHERE column LIKE '%XXXX%'
```

or

```
SELECT FROM table_name  
WHERE column LIKE 'XXXX_'
```

or

```
SELECT FROM table_name  
WHERE column LIKE '_XXXX'
```

or

```
SELECT FROM table_name  
WHERE column LIKE '_XXXX_'
```

You can combine N number of conditions using AND or OR operators. Here XXXX could be any numeric or string value.

Example:

Here are number of examples showing WHERE part having different LIKE clause with '%' and '_' operators:

Statement	Description
WHERE SALARY LIKE '200%'	Finds any values that start with 200
WHERE SALARY LIKE '%200%'	Finds any values that have 200 in any position
WHERE SALARY LIKE '_00%'	Finds any values that have 00 in the second and third positions
WHERE SALARY LIKE '2_%_%'	Finds any values that start with 2 and are at least 3 characters in length
WHERE SALARY LIKE '%2'	Finds any values that end with 2

WHERE SALARY LIKE '_2%3'

Finds any values that have a 2 in the second position and end with a 3

WHERE SALARY LIKE '2__3'

Finds any values in a five-digit number that start with 2 and end with 3

Let us take a real example, consider COMPANY table is having the following records:

ID	NAME	AGE	ADDRESS	SALARY
1	Paul	32	California	20000.0
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Following is an example, which would display all the records from COMPANY table where AGE starts with 2:

```
sqlite> SELECT * FROM COMPANY WHERE AGE LIKE '2%';
```

This would produce the following result:

ID	NAME	AGE	ADDRESS	SALARY
2	Allen	25	Texas	15000.0
3	Teddy	23	Norway	20000.0
4	Mark	25	Rich-Mond	65000.0
5	David	27	Texas	85000.0
6	Kim	22	South-Hall	45000.0
7	James	24	Houston	10000.0

Following is an example, which would display all the records from COMPANY table where ADDRESS will have a hyphen - inside the text:

```
sqlite> SELECT * FROM COMPANY WHERE ADDRESS LIKE '%-%';
```

This would produce the following result:

ID	NAME	AGE	ADDRESS	SALARY
4	Mark	25	Rich-Mond	65000.0
6	Kim	22	South-Hall	45000.0

Loading [MathJax]/jax/output/HTML-CSS/fonts/TeX/fontdata.js