



Chapter 2: Relational Model

Database System Concepts, 5th Ed.

©Silberschatz, Korth and Sudarshan

See www.db-book.com for conditions on re-use





Chapter 2: Relational Model

- Structure of Relational Databases
- Fundamental Relational-Algebra-Operations
- Additional Relational-Algebra-Operations
- Extended Relational-Algebra-Operations
- Null Values
- Modification of the Database





Example of a Relation

<i>account_number</i>	<i>branch_name</i>	<i>balance</i>
A-101	Downtown	500
A-102	Perryridge	400
A-201	Brighton	900
A-215	Mianus	700
A-217	Brighton	750
A-222	Redwood	700
A-305	Round Hill	350





Basic Structure

- Formally, given sets D_1, D_2, \dots, D_n a **relation** r is a subset of $D_1 \times D_2 \times \dots \times D_n$

Thus, a relation is a set of n -tuples (a_1, a_2, \dots, a_n) where each $a_i \in D_i$

- Example: If
 - $customer_name = \{\text{Jones, Smith, Curry, Lindsay, ...}\}$
/* Set of all customer names */
 - $customer_street = \{\text{Main, North, Park, ...}\}$ /* set of all street names*/
 - $customer_city = \{\text{Harrison, Rye, Pittsfield, ...}\}$ /* set of all city names */

Then $r = \{$
 (Jones, Main, Harrison),
 (Smith, North, Rye),
 (Curry, North, Rye),
 (Lindsay, Park, Pittsfield) $\}$

is a relation over

$customer_name \times customer_street \times customer_city$





Attribute Types

- Each attribute of a relation has a name
- The set of allowed values for each attribute is called the **domain** of the attribute
- Attribute values are (normally) required to be **atomic**; that is, indivisible
 - E.g. the value of an attribute can be an account number, but cannot be a set of account numbers
- Domain is said to be atomic if all its members are atomic
- The special value *null* is a member of every domain
- The null value causes complications in the definition of many operations
 - We shall ignore the effect of null values in our main presentation and consider their effect later





Relation Schema

- A_1, A_2, \dots, A_n are *attributes*
- $R = (A_1, A_2, \dots, A_n)$ is a *relation schema*

Example:

$Customer_schema = (customer_name, customer_street, customer_city)$

- $r(R)$ denotes a *relation* r on the *relation schema* R

Example:


$customer (Customer_schema)$





Relation Instance

- The current values (*relation instance*) of a relation are specified by a table
- An element t of r is a *tuple*, represented by a *row* in a table





Relations are Unordered

- Order of tuples is irrelevant (tuples may be stored in an arbitrary order)
- Example: *account* relation with unordered tuples

<i>account_number</i>	<i>branch_name</i>	<i>balance</i>
A-101	Downtown	500
A-215	Mianus	700
A-102	Perryridge	400
A-305	Round Hill	350
A-201	Brighton	900
A-222	Redwood	700
A-217	Brighton	750





Database

- A database consists of multiple relations
- Information about an enterprise is broken up into parts, with each relation storing one part of the information
 - account* : stores information about accounts
 - depositor* : stores information about which customer owns which account
 - customer* : stores information about customers
- Storing all information as a single relation such as
bank(account_number, balance, customer_name, ..)
results in
 - repetition of information
 - ▶ e.g.,if two customers own an account (What gets repeated?)
 - the need for null values
 - ▶ e.g., to represent a customer without an account
- Normalization theory (Chapter 7) deals with how to design relational schemas





The *customer* Relation

<i>customer_name</i>	<i>customer_street</i>	<i>customer_city</i>
Adams	Spring	Pittsfield
Brooks	Senator	Brooklyn
Curry	North	Rye
Glenn	Sand Hill	Woodside
Green	Walnut	Stamford
Hayes	Main	Harrison
Johnson	Alma	Palo Alto
Jones	Main	Harrison
Lindsay	Park	Pittsfield
Smith	North	Rye
Turner	Putnam	Stamford
Williams	Nassau	Princeton





The *depositor* Relation

<i>customer_name</i>	<i>account_number</i>
Hayes	A-102
Johnson	A-101
Johnson	A-201
Jones	A-217
Lindsay	A-222
Smith	A-215
Turner	A-305





Keys

- Let $K \subseteq R$
- K is a **superkey** of R if values for K are sufficient to identify a unique tuple of each possible relation $r(R)$
 - by “possible r ” we mean a relation r that could exist in the enterprise we are modeling.
 - Example: $\{customer_name, customer_street\}$ and $\{customer_name\}$
are both superkeys of $Customer$, if no two customers can possibly have the same name
 - ▶ In real life, an attribute such as $customer_id$ would be used instead of $customer_name$ to uniquely identify customers, but we omit it to keep our examples small, and instead assume customer names are unique.





Keys (Cont.)

- K is a **candidate key** if K is minimal

Example: $\{customer_name\}$ is a candidate key for *Customer*, since it is a superkey and no subset of it is a superkey.


- **Primary key:** a candidate key chosen as the principal means of identifying tuples within a relation
 - Should choose an attribute whose value never, or very rarely, changes.
 - E.g. email address is unique, but may change





Foreign Keys

- A relation schema may have an attribute that corresponds to the primary key of another relation. The attribute is called a **foreign key**.
 - E.g. *customer_name* and *account_number* attributes of *depositor* are foreign keys to *customer* and *account* respectively.
 - Only values occurring in the primary key attribute of the **referenced relation** may occur in the foreign key attribute of the **referencing relation**.
- **Schema diagram**





Query Languages

- Language in which user requests information from the database.
- Categories of languages
 - Procedural
 - Non-procedural, or declarative
- “Pure” languages:
 - Relational algebra
 - Tuple relational calculus
 - Domain relational calculus
- Pure languages form underlying basis of query languages that people use.





Relational Algebra

- Procedural language
- Six basic operators
 - select: σ
 - project: Π
 - union: \cup
 - set difference: $-$
 - Cartesian product: \times
 - rename: ρ
- The operators take one or two relations as inputs and produce a new relation as a result.





Select Operation – Example

- Relation r

A	B	C	D
α	α	1	7
α	β	5	7
β	β	12	3
β	β	23	10

- $\sigma_{A=B \wedge D > 5}(r)$

A	B	C	D
α	α	1	7
β	β	23	10





Select Operation

- Notation: $\sigma_p(r)$
- p is called the **selection predicate**
- Defined as:

$$\sigma_p(r) = \{t \mid t \in r \text{ and } p(t)\}$$

Where p is a formula in propositional calculus consisting of **terms** connected by : \wedge (**and**), \vee (**or**), \neg (**not**)
Each **term** is one of:

$\langle \text{attribute} \rangle \quad op \quad \langle \text{attribute} \rangle$ or $\langle \text{constant} \rangle$

where op is one of: $=, \neq, >, \geq, <, \leq$

- Example of selection:

$$\sigma_{\text{branch_name}=\text{"Perryridge"}}(\text{account})$$





Project Operation – Example

■ Relation r :

A	B	C
α	10	1
α	20	1
β	30	1
β	40	2

$\Pi_{A,C}(r)$

A	C
α	1
α	1
β	1
β	2

=

A	C
α	1
β	1
β	2





Project Operation

- Notation:

$$\Pi_{A_1, A_2, \dots, A_k}(r)$$

where A_1, A_2 are attribute names and r is a relation name.

- The result is defined as the relation of k columns obtained by erasing the columns that are not listed
- Duplicate rows removed from result, since relations are sets
- Example: To eliminate the *branch_name* attribute of *account*

$$\Pi_{\text{account_number, balance}}(\text{account})$$





Union Operation – Example

- Relations r, s :

A	B
α	1
α	2
β	1

r

A	B
α	2
β	3

s

- $r \cup s$:

A	B
α	1
α	2
β	1
β	3





Union Operation

- Notation: $r \cup s$
- Defined as:

$$r \cup s = \{t \mid t \in r \text{ or } t \in s\}$$

- For $r \cup s$ to be valid.
 1. r, s must have the **same arity** (same number of attributes)
 2. The attribute domains must be **compatible** (example: 2nd column of r deals with the same type of values as does the 2nd column of s)
- Example: to find all customers with either an account or a loan

$$\Pi_{customer_name}(depositor) \cup \Pi_{customer_name}(borrower)$$





Set Difference Operation – Example

- Relations r , s :

A	B
α	1
α	2
β	1

r

A	B
α	2
β	3

s

- $r - s$:

A	B
α	1
β	1





Set Difference Operation

- Notation $r - s$
- Defined as:

$$r - s = \{t \mid t \in r \text{ and } t \notin s\}$$

- Set differences must be taken between **compatible** relations.
 - r and s must have the **same** arity
 - attribute domains of r and s must be compatible





Cartesian-Product Operation – Example

■ Relations r, s :

A	B
α	1
β	2

r

C	D	E
α	10	a
β	10	a
β	20	b
γ	10	b

s

■ $r \times s$:

A	B	C	D	E
α	1	α	10	a
α	1	β	10	a
α	1	β	20	b
α	1	γ	10	b
β	2	α	10	a
β	2	β	10	a
β	2	β	20	b
β	2	γ	10	b





Cartesian-Product Operation

- Notation $r \times s$
- Defined as:

$$r \times s = \{t q \mid t \in r \text{ and } q \in s\}$$

- Assume that attributes of $r(R)$ and $s(S)$ are disjoint. (That is, $R \cap S = \emptyset$).
- If attributes of $r(R)$ and $s(S)$ are not disjoint, then renaming must be used.





Composition of Operations

- Can build expressions using multiple operations
- Example: $\sigma_{A=C}(r \times s)$

■ $r \times s$

<i>A</i>	<i>B</i>	<i>C</i>	<i>D</i>	<i>E</i>
α	1	α	10	<i>a</i>
α	1	β	10	<i>a</i>
α	1	β	20	<i>b</i>
α	1	γ	10	<i>b</i>
β	2	α	10	<i>a</i>
β	2	β	10	<i>a</i>
β	2	β	20	<i>b</i>
β	2	γ	10	<i>b</i>

■ $\sigma_{A=C}(r \times s)$

<i>A</i>	<i>B</i>	<i>C</i>	<i>D</i>	<i>E</i>
α	1	α	10	<i>a</i>
β	2	β	10	<i>a</i>
β	2	β	20	<i>b</i>





Rename Operation

- Allows us to name, and therefore to refer to, the results of relational-algebra expressions.
- Allows us to refer to a relation by more than one name.
- Example:

$$\rho_X(E)$$

returns the expression E under the name X

- If a relational-algebra expression E has arity n , then

$$\rho_{X(A_1, A_2, \dots, A_n)}(E)$$

returns the result of expression E under the name X , and with the attributes renamed to A_1, A_2, \dots, A_n .





Banking Example

branch (branch_name, branch_city, assets)

customer (customer_name, customer_street, customer_city)

account (account_number, branch_name, balance)

loan (loan_number, branch_name, amount)

depositor (customer_name, account_number)

borrower (customer_name, loan_number)





Example Queries

- Find all loans of over \$1200

$$\sigma_{amount > 1200} (loan)$$

- Find the loan number for each loan of an amount greater than \$1200

$$\Pi_{loan_number} (\sigma_{amount > 1200} (loan))$$

- Find the names of all customers who have a loan, an account, or both, from the bank

$$\Pi_{customer_name} (borrower) \cup \Pi_{customer_name} (depositor)$$





Example Queries

- Find the names of all customers who have a loan at the Perryridge branch.

$$\Pi_{customer_name} (\sigma_{branch_name="Perryridge"} (\sigma_{borrower.loan_number = loan.loan_number} (borrower \times loan)))$$

- Find the names of all customers who have a loan at the Perryridge branch but do not have an account at any branch of the bank.

$$\Pi_{customer_name} (\sigma_{branch_name = "Perryridge"} (\sigma_{borrower.loan_number = loan.loan_number} (borrower \times loan))) - \Pi_{customer_name} (depositor)$$




Example Queries

- Find the names of all customers who have a loan at the Perryridge branch.

- Query 1

$$\Pi_{\text{customer_name}} (\sigma_{\text{branch_name} = \text{"Perryridge"}} (\sigma_{\text{borrower.loan_number} = \text{loan.loan_number}} (\text{borrower} \times \text{loan})))$$

- Query 2

$$\Pi_{\text{customer_name}} (\sigma_{\text{loan.loan_number} = \text{borrower.loan_number}} (\sigma_{\text{branch_name} = \text{"Perryridge"}} (\text{loan}) \times \text{borrower}))$$




Example Queries

- Find the largest account balance
 - Strategy:
 - ▶ Find those balances that are *not* the largest
 - Rename *account* relation as *d* so that we can compare each account balance with all others
 - ▶ Use set difference to find those account balances that were *not* found in the earlier step.
 - The query is:

$$\Pi_{balance}(account) - \Pi_{account.balance}(\sigma_{account.balance < d.balance}(account \times \rho_d(account)))$$





Formal Definition

- A basic expression in the relational algebra consists of either one of the following:
 - A relation in the database
 - A constant relation
- Let E_1 and E_2 be relational-algebra expressions; the following are all relational-algebra expressions:
 - $E_1 \cup E_2$
 - $E_1 - E_2$
 - $E_1 \times E_2$
 - $\sigma_P(E_1)$, P is a predicate on attributes in E_1
 - $\Pi_S(E_1)$, S is a list consisting of some of the attributes in E_1
 - $\rho_x(E_1)$, x is the new name for the result of E_1





Additional Operations

We define additional operations that do not add any power to the relational algebra, but that simplify common queries.

- Set intersection
- Natural join
- Division
- Assignment





Set-Intersection Operation

- Notation: $r \cap s$
- Defined as:
- $r \cap s = \{ t \mid t \in r \text{ and } t \in s \}$
- Assume:
 - r, s have the *same arity*
 - attributes of r and s are compatible
- Note: $r \cap s = r - (r - s)$





Set-Intersection Operation – Example

- Relation r, s :

A	B
α	1
α	2
β	1

r

A	B
α	2
β	3

s

- $r \cap s$

A	B
α	2





Natural-Join Operation

- Notation: $r \bowtie s$
- Let r and s be relations on schemas R and S respectively. Then, $r \bowtie s$ is a relation on schema $R \cup S$ obtained as follows:
 - Consider each pair of tuples t_r from r and t_s from s .
 - If t_r and t_s have the same value on each of the attributes in $R \cap S$, add a tuple t to the result, where
 - ▶ t has the same value as t_r on r
 - ▶ t has the same value as t_s on s

- Example:

$R = (A, B, C, D)$

$S = (E, B, D)$

- Result schema = (A, B, C, D, E)
- $r \bowtie s$ is defined as:

$$\Pi_{r.A, r.B, r.C, r.D, s.E} (\sigma_{r.B = s.B \wedge r.D = s.D} (r \times s))$$





Natural Join Operation – Example

- Relations r , s :

A	B	C	D
α	1	α	a
β	2	γ	a
γ	4	β	b
α	1	γ	a
δ	2	β	b

r

B	D	E
1	a	α
3	a	β
1	a	γ
2	b	δ
3	b	ϵ

s

- $r \bowtie s$

A	B	C	D	E
α	1	α	a	α
α	1	α	a	γ
α	1	γ	a	α
α	1	γ	a	γ
δ	2	β	b	δ





Division Operation

- Notation: $r \div s$
- Suited to queries that include the phrase “for all”.
- Let r and s be relations on schemas R and S respectively where
 - $R = (A_1, \dots, A_m, B_1, \dots, B_n)$
 - $S = (B_1, \dots, B_n)$

The result of $r \div s$ is a relation on schema

$$R - S = (A_1, \dots, A_m)$$

$$r \div s = \{ t \mid t \in \Pi_{R-S}(r) \wedge \forall u \in s (tu \in r) \}$$

Where tu means the concatenation of tuples t and u to produce a single tuple





Division Operation – Example

■ Relations r, s :

A	B
α	1
α	2
α	3
β	1
γ	1
δ	1
δ	3
δ	4
ϵ	6
ϵ	1
β	2

r

B
1
2

s

■ $r \div s$:

A
α
β





Another Division Example

- Relations r, s :

A	B	C	D	E
α	a	α	a	1
α	a	γ	a	1
α	a	γ	b	1
β	a	γ	a	1
β	a	γ	b	3
γ	a	γ	a	1
γ	a	γ	b	1
γ	a	β	b	1

r

D	E
a	1
b	1

s

- $r \div s$:

A	B	C
α	a	γ
γ	a	γ





Division Operation (Cont.)

- Property
 - Let $q = r \div s$
 - Then q is the largest relation satisfying $q \times s \subseteq r$
 - Definition in terms of the basic algebra operation
- Let $r(R)$ and $s(S)$ be relations, and let $S \subseteq R$

$$r \div s = \Pi_{R-S}(r) - \Pi_{R-S}((\Pi_{R-S}(r) \times s) - \Pi_{R-S,S}(r))$$

To see why

- $\Pi_{R-S,S}(r)$ simply reorders attributes of r
- $\Pi_{R-S}(\Pi_{R-S}(r) \times s) - \Pi_{R-S,S}(r)$ gives those tuples t in $\Pi_{R-S}(r)$ such that for some tuple $u \in s$, $tu \notin r$.





Assignment Operation

- The assignment operation (\leftarrow) provides a convenient way to express complex queries.
 - Write query as a sequential program consisting of
 - ▶ a series of assignments
 - ▶ followed by an expression whose value is displayed as a result of the query.
 - Assignment must always be made to a temporary relation variable.
- Example: Write $r \div s$ as

$$temp1 \leftarrow \Pi_{R-S}(r)$$

$$temp2 \leftarrow \Pi_{R-S}((temp1 \times s) - \Pi_{R-S,S}(r))$$

$$result = temp1 - temp2$$

- The result to the right of the \leftarrow is assigned to the relation variable on the left of the \leftarrow .
- May use variable in subsequent expressions.





Bank Example Queries

- Find the names of all customers who have a loan and an account at bank.

$$\Pi_{customer_name} (borrower) \cap \Pi_{customer_name} (depositor)$$

- Find the name of all customers who have a loan at the bank and the loan amount

$$\Pi_{customer_name, loan_number, amount} (borrower \bowtie loan)$$





Bank Example Queries

- Find all customers who have an account from at least the “Downtown” and the Uptown” branches.

- Query 1

$$\Pi_{customer_name} (\sigma_{branch_name = \text{“Downtown”}} (depositor \bowtie account)) \cap \Pi_{customer_name} (\sigma_{branch_name = \text{“Uptown”}} (depositor \bowtie account))$$

- Query 2

$$\Pi_{customer_name, branch_name} (depositor \bowtie account) \div \rho_{temp(branch_name)} (\{(\text{“Downtown”}), (\text{“Uptown”})\})$$

Note that Query 2 uses a constant relation.





Bank Example Queries

- Find all customers who have an account at all branches located in Brooklyn city.

$$\Pi_{customer_name, branch_name} (depositor \bowtie account) \\ \div \Pi_{branch_name} (\sigma_{branch_city = \text{“Brooklyn”}} (branch))$$





Extended Relational-Algebra-Operations

- Generalized Projection
- Aggregate Functions
- Outer Join





Generalized Projection

- Extends the projection operation by allowing arithmetic functions to be used in the projection list.

$$\Pi_{F_1, F_2, \dots, F_n}(E)$$

- E is any relational-algebra expression
- Each of F_1, F_2, \dots, F_n are arithmetic expressions involving constants and attributes in the schema of E .
- Given relation $credit_info(customer_name, limit, credit_balance)$, find how much more each person can spend:

$$\Pi_{customer_name, limit - credit_balance}(credit_info)$$





Aggregate Functions and Operations

- **Aggregation function** takes a collection of values and returns a single value as a result.

avg: average value

min: minimum value

max: maximum value

sum: sum of values

count: number of values

- **Aggregate operation** in relational algebra

$$G_1, G_2, \dots, G_n \mathcal{G}_{F_1(A_1), F_2(A_2), \dots, F_n(A_n)}(E)$$

E is any relational-algebra expression

- G_1, G_2, \dots, G_n is a list of attributes on which to group (can be empty)
- Each F_i is an aggregate function
- Each A_i is an attribute name





Aggregate Operation – Example

- Relation r :

A	B	C
α	α	7
α	β	7
β	β	3
β	β	10

- $g_{\text{sum}(c)}(r)$

sum(c)
27





Aggregate Operation – Example

- Relation *account* grouped by *branch-name*:

<i>branch_name</i>	<i>account_number</i>	<i>balance</i>
Perryridge	A-102	400
Perryridge	A-201	900
Brighton	A-217	750
Brighton	A-215	750
Redwood	A-222	700

branch_name \mathcal{G} **sum**(*balance*) (*account*)

<i>branch_name</i>	sum (<i>balance</i>)
Perryridge	1300
Brighton	1500
Redwood	700





Aggregate Functions (Cont.)

- Result of aggregation does not have a name
 - Can use rename operation to give it a name
 - For convenience, we permit renaming as part of aggregate operation

branch_name \mathcal{G} **sum**(*balance*) **as** *sum_balance* (*account*)





Outer Join

- An extension of the join operation that avoids loss of information.
- Computes the join and then adds tuples from one relation that does not match tuples in the other relation to the result of the join.
- Uses *null* values:
 - *null* signifies that the value is unknown or does not exist
 - All comparisons involving *null* are (roughly speaking) **false** by definition.
 - ▶ We shall study precise meaning of comparisons with nulls later





Outer Join – Example

- Relation *loan*

<i>loan_number</i>	<i>branch_name</i>	<i>amount</i>
L-170	Downtown	3000
L-230	Redwood	4000
L-260	Perryridge	1700

- Relation *borrower*

<i>customer_name</i>	<i>loan_number</i>
Jones	L-170
Smith	L-230
Hayes	L-155





Outer Join – Example

■ Join

loan ⋈ *borrower*

<i>loan_number</i>	<i>branch_name</i>	<i>amount</i>	<i>customer_name</i>
L-170	Downtown	3000	Jones
L-230	Redwood	4000	Smith

■ Left Outer Join

loan ⋈_L *borrower*

<i>loan_number</i>	<i>branch_name</i>	<i>amount</i>	<i>customer_name</i>
L-170	Downtown	3000	Jones
L-230	Redwood	4000	Smith
L-260	Perryridge	1700	<i>null</i>





Outer Join – Example

■ Right Outer Join

loan ⋈_⊃ *borrower*

<i>loan_number</i>	<i>branch_name</i>	<i>amount</i>	<i>customer_name</i>
L-170	Downtown	3000	Jones
L-230	Redwood	4000	Smith
L-155	<i>null</i>	<i>null</i>	Hayes

■ Full Outer Join

loan ⋈_{⊃⊂} *borrower*

<i>loan_number</i>	<i>branch_name</i>	<i>amount</i>	<i>customer_name</i>
L-170	Downtown	3000	Jones
L-230	Redwood	4000	Smith
L-260	Perryridge	1700	<i>null</i>
L-155	<i>null</i>	<i>null</i>	Hayes





Null Values

- It is possible for tuples to have a null value, denoted by *null*, for some of their attributes
- *null* signifies an unknown value or that a value does not exist.
- The result of any arithmetic expression involving *null* is *null*.
- Aggregate functions simply ignore null values (as in SQL)
- For duplicate elimination and grouping, null is treated like any other value, and two nulls are assumed to be the same (as in SQL)





Null Values

- Comparisons with null values return the special truth value: *unknown*
 - If *false* was used instead of *unknown*, then $\text{not } (A < 5)$ would not be equivalent to $A \geq 5$
- Three-valued logic using the truth value *unknown*:
 - OR: $(\text{unknown or true}) = \text{true}$,
 $(\text{unknown or false}) = \text{unknown}$
 $(\text{unknown or unknown}) = \text{unknown}$
 - AND: $(\text{true and unknown}) = \text{unknown}$,
 $(\text{false and unknown}) = \text{false}$,
 $(\text{unknown and unknown}) = \text{unknown}$
 - NOT: $(\text{not unknown}) = \text{unknown}$
 - In SQL “*P is unknown*” evaluates to true if predicate *P* evaluates to *unknown*
- Result of select predicate is treated as *false* if it evaluates to *unknown*





Modification of the Database

- The content of the database may be modified using the following operations:
 - Deletion
 - Insertion
 - Updating
- All these operations are expressed using the assignment operator.





Deletion

- A delete request is expressed similarly to a query, except instead of displaying tuples to the user, the selected tuples are removed from the database.
- Can delete only whole tuples; cannot delete values on only particular attributes
- A deletion is expressed in relational algebra by:

$$r \leftarrow r - E$$

where r is a relation and E is a relational algebra query.





Deletion Examples

- Delete all account records in the Perryridge branch.

$account \leftarrow account - \sigma_{branch_name = "Perryridge"}(account)$

- Delete all loan records with amount in the range of 0 to 50

$loan \leftarrow loan - \sigma_{amount \geq 0 \text{ and } amount \leq 50}(loan)$

- Delete all accounts at branches located in Needham.

$r_1 \leftarrow \sigma_{branch_city = "Needham"}(account \bowtie branch)$

$r_2 \leftarrow \Pi_{account_number, branch_name, balance}(r_1)$

$r_3 \leftarrow \Pi_{customer_name, account_number}(r_2 \bowtie depositor)$

$account \leftarrow account - r_2$

$depositor \leftarrow depositor - r_3$





Insertion

- To insert data into a relation, we either:
 - specify a tuple to be inserted
 - write a query whose result is a set of tuples to be inserted
- in relational algebra, an insertion is expressed by:

$$r \leftarrow r \cup E$$

where r is a relation and E is a relational algebra expression.

- The insertion of a single tuple is expressed by letting E be a constant relation containing one tuple.





Insertion Examples

- Insert information in the database specifying that Smith has \$1200 in account A-973 at the Perryridge branch.

$$account \leftarrow account \cup \{("A-973", "Perryridge", 1200)\}$$
$$depositor \leftarrow depositor \cup \{("Smith", "A-973")\}$$

- Provide as a gift for all loan customers in the Perryridge branch, a \$200 savings account. Let the loan number serve as the account number for the new savings account.

$$r_1 \leftarrow (\sigma_{branch_name = "Perryridge"}(borrower \bowtie loan))$$
$$account \leftarrow account \cup \Pi_{loan_number, branch_name, 200}(r_1)$$
$$depositor \leftarrow depositor \cup \Pi_{customer_name, loan_number}(r_1)$$




Updating

- A mechanism to change a value in a tuple without changing *all* values in the tuple
- Use the generalized projection operator to do this task

$$r \leftarrow \Pi_{F_1, F_2, \dots, F_l}(r)$$

- Each F_i is either
 - the i^{th} attribute of r , if the i^{th} attribute is not updated, or,
 - if the attribute is to be updated F_i is an expression, involving only constants and the attributes of r , which gives the new value for the attribute





Update Examples

- Make interest payments by increasing all balances by 5 percent.

$$account \leftarrow \Pi_{account_number, branch_name, balance * 1.05} (account)$$

- Pay all accounts with balances over \$10,000 6 percent interest and pay all others 5 percent

$$account \leftarrow \Pi_{account_number, branch_name, balance * 1.06} (\sigma_{BAL > 10000} (account)) \cup \Pi_{account_number, branch_name, balance * 1.05} (\sigma_{BAL \leq 10000} (account))$$




End of Chapter 2

Database System Concepts, 5th Ed.

©Silberschatz, Korth and Sudarshan

See www.db-book.com for conditions on re-use





Figure 2.3. The *branch* relation

<i>branch_name</i>	<i>branch_city</i>	<i>assets</i>
Brighton	Brooklyn	7100000
Downtown	Brooklyn	9000000
Mianus	Horseneck	400000
North Town	Rye	3700000
Perryridge	Horseneck	1700000
Pownal	Bennington	300000
Redwood	Palo Alto	2100000
Round Hill	Horseneck	8000000





Figure 2.6: The *loan* relation

<i>loan_number</i>	<i>branch_name</i>	<i>amount</i>
L-11	Round Hill	900
L-14	Downtown	1500
L-15	Perryridge	1500
L-16	Perryridge	1300
L-17	Downtown	1000
L-23	Redwood	2000
L-93	Mianus	500





Figure 2.7: The *borrower* relation

<i>customer_name</i>	<i>loan_number</i>
Adams	L-16
Curry	L-93
Hayes	L-15
Jackson	L-14
Jones	L-17
Smith	L-11
Smith	L-23
Williams	L-17





Figure 2.9

Result of $\sigma_{\text{branch_name} = \text{"Perryridge"}}$ (*loan*)

<i>loan_number</i>	<i>branch_name</i>	<i>amount</i>
L-15	Perryridge	1500
L-16	Perryridge	1300





Figure 2.10:

Loan number and the amount of the loan

<i>loan_number</i>	<i>amount</i>
L-11	900
L-14	1500
L-15	1500
L-16	1300
L-17	1000
L-23	2000
L-93	500





Figure 2.11: Names of all customers who have either an account or an loan

<i>customer_name</i>
Adams
Curry
Hayes
Jackson
Jones
Smith
Williams
Lindsay
Johnson
Turner





Figure 2.12: Customers with an account but no loan

<i>customer_name</i>
Johnson
Lindsay
Turner





Figure 2.13: Result of *borrower |X| loan*

<i>customer_name</i>	<i>borrower. loan_number</i>	<i>loan. loan_number</i>	<i>branch_name</i>	<i>amount</i>
Adams	L-16	L-11	Round Hill	900
Adams	L-16	L-14	Downtown	1500
Adams	L-16	L-15	Perryridge	1500
Adams	L-16	L-16	Perryridge	1300
Adams	L-16	L-17	Downtown	1000
Adams	L-16	L-23	Redwood	2000
Adams	L-16	L-93	Mianus	500
Curry	L-93	L-11	Round Hill	900
Curry	L-93	L-14	Downtown	1500
Curry	L-93	L-15	Perryridge	1500
Curry	L-93	L-16	Perryridge	1300
Curry	L-93	L-17	Downtown	1000
Curry	L-93	L-23	Redwood	2000
Curry	L-93	L-93	Mianus	500
Hayes	L-15	L-11		900
Hayes	L-15	L-14		1500
Hayes	L-15	L-15		1500
Hayes	L-15	L-16		1300
Hayes	L-15	L-17		1000
Hayes	L-15	L-23		2000
Hayes	L-15	L-93		500
...
...
...
Smith	L-23	L-11	Round Hill	900
Smith	L-23	L-14	Downtown	1500
Smith	L-23	L-15	Perryridge	1500
Smith	L-23	L-16	Perryridge	1300
Smith	L-23	L-17	Downtown	1000
Smith	L-23	L-23	Redwood	2000
Smith	L-23	L-93	Mianus	500
Williams	L-17	L-11	Round Hill	900
Williams	L-17	L-14	Downtown	1500
Williams	L-17	L-15	Perryridge	1500
Williams	L-17	L-16	Perryridge	1300
Williams	L-17	L-17	Downtown	1000
Williams	L-17	L-23	Redwood	2000
Williams	L-17	L-93	Mianus	500





Figure 2.14

<i>customer_name</i>	<i>borrower. loan_number</i>	<i>loan. loan_number</i>	<i>branch_name</i>	<i>amount</i>
Adams	L-16	L-15	Perryridge	1500
Adams	L-16	L-16	Perryridge	1300
Curry	L-93	L-15	Perryridge	1500
Curry	L-93	L-16	Perryridge	1300
Hayes	L-15	L-15	Perryridge	1500
Hayes	L-15	L-16	Perryridge	1300
Jackson	L-14	L-15	Perryridge	1500
Jackson	L-14	L-16	Perryridge	1300
Jones	L-17	L-15	Perryridge	1500
Jones	L-17	L-16	Perryridge	1300
Smith	L-11	L-15	Perryridge	1500
Smith	L-11	L-16	Perryridge	1300
Smith	L-23	L-15	Perryridge	1500
Smith	L-23	L-16	Perryridge	1300
Williams	L-17	L-15	Perryridge	1500
Williams	L-17	L-16	Perryridge	1300





Figure 2.15

<i>customer_name</i>
Adams
Hayes





Figure 2.16

<i>balance</i>
500
400
700
750
350





Figure 2.17

Largest account balance in the bank

<i>balance</i>
900





Figure 2.18: Customers who live on the same street and in the same city as Smith

<i>customer_name</i>
Curry Smith





Figure 2.19: Customers with both an account and a loan at the bank

<i>customer_name</i>
Hayes
Jones
Smith





Figure 2.20

<i>customer_name</i>	<i>loan_number</i>	<i>amount</i>
Adams	L-16	1300
Curry	L-93	500
Hayes	L-15	1500
Jackson	L-14	1500
Jones	L-17	1000
Smith	L-23	2000
Smith	L-11	900
Williams	L-17	1000





Figure 2.21

<i>branch_name</i>
Brighton
Perryridge





Figure 2.22

<i>branch_name</i>
Brighton
Downtown





Figure 2.23

<i>customer_name</i>	<i>branch_name</i>
Hayes	Perryridge
Johnson	Downtown
Johnson	Brighton
Jones	Brighton
Lindsay	Redwood
Smith	Mianus
Turner	Round Hill





Figure 2.24: The *credit_info* relation

<i>customer_name</i>	<i>limit</i>	<i>credit_balance</i>
Curry	2000	1750
Hayes	1500	1500
Jones	6000	700
Smith	2000	400





Figure 2.25

<i>customer_name</i>	<i>credit_available</i>
Curry	250
Jones	5300
Smith	1600
Hayes	0





Figure 2.26: The *pt_works* relation

<i>employee_name</i>	<i>branch_name</i>	<i>salary</i>
Adams	Perryridge	1500
Brown	Perryridge	1300
Gopal	Perryridge	5300
Johnson	Downtown	1500
Loreena	Downtown	1300
Peterson	Downtown	2500
Rao	Austin	1500
Sato	Austin	1600





Figure 2.27

The *pt_works* relation after regrouping

<i>employee_name</i>	<i>branch_name</i>	<i>salary</i>
Rao	Austin	1500
Sato	Austin	1600
Johnson	Downtown	1500
Loreena	Downtown	1300
Peterson	Downtown	2500
Adams	Perryridge	1500
Brown	Perryridge	1300
Gopal	Perryridge	5300





Figure 2.28

<i>branch_name</i>	<i>sum of salary</i>
Austin	3100
Downtown	5300
Perryridge	8100





Figure 2.29

<i>branch_name</i>	<i>sum_salary</i>	<i>max_salary</i>
Austin	3100	1600
Downtown	5300	2500
Perryridge	8100	5300





Figure 2.30

The *employee* and *ft_works* relations

<i>employee_name</i>	<i>street</i>	<i>city</i>
Coyote	Toon	Hollywood
Rabbit	Tunnel	Carrotville
Smith	Revolver	Death Valley
Williams	Seaview	Seattle

<i>employee_name</i>	<i>branch_name</i>	<i>salary</i>
Coyote	Mesa	1500
Rabbit	Mesa	1300
Gates	Redmond	5300
Williams	Redmond	1500





Figure 2.31

<i>employee_name</i>	<i>street</i>	<i>city</i>	<i>branch_name</i>	<i>salary</i>
Coyote	Toon	Hollywood	Mesa	1500
Rabbit	Tunnel	Carrotville	Mesa	1300
Williams	Seaview	Seattle	Redmond	1500





Figure 2.32

<i>employee_name</i>	<i>street</i>	<i>city</i>	<i>branch_name</i>	<i>salary</i>
Coyote	Toon	Hollywood	Mesa	1500
Rabbit	Tunnel	Carrotville	Mesa	1300
Williams	Seaview	Seattle	Redmond	1500
Smith	Revolver	Death Valley	<i>null</i>	<i>null</i>





Figure 2.33

<i>employee_name</i>	<i>street</i>	<i>city</i>	<i>branch_name</i>	<i>salary</i>
Coyote	Toon	Hollywood	Mesa	1500
Rabbit	Tunnel	Carrotville	Mesa	1300
Williams	Seaview	Seattle	Redmond	1500
Gates	<i>null</i>	<i>null</i>	Redmond	5300





Figure 2.34

<i>employee_name</i>	<i>street</i>	<i>city</i>	<i>branch_name</i>	<i>salary</i>
Coyote	Toon	Hollywood	Mesa	1500
Rabbit	Tunnel	Carrotville	Mesa	1300
Williams	Seaview	Seattle	Redmond	1500
Smith	Revolver	Death Valley	<i>null</i>	<i>null</i>
Gates	<i>null</i>	<i>null</i>	Redmond	5300

